











亦可做中心出水鋼柄
A- Steel shank with coolant

Order No.	Insert	Dimensions(mm)					Parts				Wrench
		柄徑	工作寬度	長度	最小加工徑	徑向前角					
Right / Left		DCON	WF	LF	DMIN	GAMF					
S12M-CTUPR/L11	TPMN1103	12	9	150	18	6°	-	-	CP50-27S		LW025
S16Q-CTUPR/L11		16	11	180	20	3°	-	-	CP50-21	CS7-5015	LW025
S20R-CTUPR/L11		20	13	200	25	3°	-	-	CP50-21	CS7-5015	LW025
S25R-CTUPR/L16	TPMN1603	25	17	200	32	3°	SMT-321	CS20045	CP50-22	CS7-6024	LW030
S32S-CTUPR/L16		32	22	250	40	3°	SMT-321	CS20045	CP50-22	CS7-6024	LW030



亦可做中心出水鋼柄
A- Steel shank with coolant

Order No.	Insert	Dimensions(mm)					Parts					Wrench	
		柄徑	工作寬度	長度	最小加工徑	徑向前角							
Right / Left		DCON	WF	LF	DMIN	GAMF							
S25R-DCLNR/L12	CNMG1204	25	17	200	32	14°	SMC-422	CSF4010	CP-D4	SP0816	CSB0620T	TL20	LW025
S32S-DCLNR/L12		32	22	250	40	14°	SMC-422	CSF4010	CP-D4	SP0816	CSB0620T	TL20	LW025
S40T-DCLNR/L12		40	27	300	50	12°	SMC-422	CSF4010	CP-D4	SP0816	CSB0620T	TL20	LW025



亦可做中心出水鋼柄
A- Steel shank with coolant

Order No.	Insert	Dimensions(mm)					Parts					Wrench	
		柄徑	工作寬度	長度	最小加工徑	徑向前角							
Right / Left		DCON	WF	LF	DMIN	GAMF							
S25R-DDUNR/L15	DNMG1504-SMD443	25	17	200	32	16°	SMD-4XX	CSF4010	CP-D4	SP0816	CSB0620T	TL20	LW025
S32S-DDUNR/L15	DNMG1506-SMD424	32	22	250	40	12°	SMD-4XX	CSF4010	CP-D4	SP0816	CSB0620T	TL20	LW025
S40T-DDUNR/L15		40	27	300	50	10°	SMD-4XX	CSF4010	CP-D4	SP0816	CSB0620T	TL20	LW025