



Order No.	Insert	Dimensions(mm)					Parts	Wrench	
		柄徑	工作寬度	長度	最小加工徑	徑向前角			
Right / Left		DCON	WF	LF	DMIN	GAMF			
S08K-STUCR/L09-10	TCMT0902	8	5	125	10	15°	CS22050	FT-7	
S10K-STUCR09-12		10	6	125	12	13°	CS22050	FT-7	
S10K-STUCR11	TCMT1102	10	7	125	14	12°	CS25061S	FT-7	
S10K-STUCR11-12		10	6	125	12	12°	CS25061S	FT-7	
S12M-STUCR11-14		12	7	150	14	10°	CS25061S	FT-7	
S16Q-STUCR11		16	11	180	18	8°	CS25061S	FT-7	
S16Q-STUCR11-18		16	9	180	18	8°	CS25061S	FT-7	
S20R-STUCR11-22		20	11	200	22	6°	CS25061S	FT-7	
S25R-STUCR1102-28		25	14	200	28	6°	CS25061S	FT-7	
S32S-STUCR1102		32	22	250	39	4°	CS25061S	FT-7	
S20R-STUCR16		TCMT16T3	20	13	200	25	6°	CS35090	FT-15
S20R-STUCR16-22			20	11	200	22	6°	CS35090	FT-15
S25R-STUCR16	25		17	200	32	6°	CS35090	FT-15	
S25R-STUCR16-28	25		14	200	28	6°	CS35090	FT-15	
S32S-STUCR16	32		22	250	39	4°	CS35090	FT-15	

A- Steel shank with coolant
亦可做中心出水鋼柄