



S-SCLC
S-SCLC-S
95°



亦可做中心出水鋼柄
A- Steel shank with coolant

| Order No. | Insert | Dimensions(mm) | | | | | Parts | | | Wrench | |
|-------------------|----------|----------------|------------|----------|---------------|--------------|---------|-------|----------|--------|-------|
| | | 柄徑 DCON | 工作寬度 WF | 長度 LF | 最小加工徑 DMIN | 徑向前角 GAMF | | | | | |
| S08H-SCLCR/L06 | CCMT0602 | 8 | 6 | 100 | 12 | 13° | - | - | CS25050 | FT-7 | - |
| S08H-SCLCR/L06-10 | | 8 | 5 | 100 | 10 | 13° | - | - | CS25050 | FT-7 | - |
| S10K-SCLCR/L06 | | 10 | 7 | 125 | 14 | 12° | - | - | CS25061S | FT-7 | - |
| S10K-SCLCR/L06-12 | | 10 | 6 | 125 | 12 | 12° | - | - | CS25061S | FT-7 | - |
| S12M-SCLCR/L06 | | 12 | 9 | 150 | 16 | 9° | - | - | CS25061S | FT-7 | - |
| S12M-SCLCR/L06-14 | | 12 | 7 | 150 | 14 | 9° | - | - | CS25061S | FT-7 | - |
| S16Q-SCLCR/L06 | | 16 | 11 | 180 | 20 | 7° | - | - | CS25061S | FT-7 | - |
| S16Q-SCLCR/L06-18 | | 16 | 9 | 180 | 18 | 7° | - | - | CS25061S | FT-7 | - |
| S08H-SCLCR08 | CCMT0804 | 8 | 6 | 100 | 12 | 12° | - | - | CS30070 | FT-10 | - |
| S10K-SCLCR08 | | 10 | 7 | 125 | 14 | 12° | - | - | CS30070 | FT-10 | - |
| S10K-SCLCR08-12 | | 10 | 6 | 125 | 12 | 12° | - | - | CS30070 | FT-10 | - |
| S12M-SCLCR08-14 | | 12 | 7 | 150 | 14 | 12° | - | - | CS30070 | FT-10 | - |
| S16Q-SCLCR08-18 | | 16 | 9 | 180 | 18 | 9° | - | - | CS30070 | FT-10 | - |
| S20R-SCLCR08-22 | | 20 | 11 | 200 | 22 | 7° | - | - | CS30070 | FT-10 | - |
| S12M-SCLCR/L09 | CCMT09T3 | 12 | 9 | 150 | 16 | 13° | - | - | CS35075 | FT-15 | - |
| S12M-SCLCR/L09-14 | | 12 | 7 | 150 | 14 | 13° | - | - | CS35075 | FT-15 | - |
| S16Q-SCLCR/L09 | | 16 | 11 | 180 | 20 | 9° | - | - | CS35075 | FT-15 | - |
| S16Q-SCLCR/L09-18 | | 16 | 9 | 180 | 18 | 9° | - | - | CS35075 | FT-15 | - |
| S20R-SCLCR/L09 | | 20 | 13 | 200 | 25 | 7° | - | - | CS35090 | FT-15 | - |
| S20S-SCLCR/L09 | | 20 | 13 | 250 | 25 | 7° | - | - | CS35090 | FT-15 | - |
| S20R-SCLCR/L09-22 | | 20 | 11 | 200 | 22 | 5° | - | - | CS35090 | FT-15 | - |
| S25R-SCLCR/L09 | | 25 | 17 | 200 | 32 | 5° | - | - | CS35090 | FT-15 | - |
| S25R-SCLCR/L09-28 | | 25 | 14.5 | 200 | 28 | 5° | - | - | CS35090 | FT-15 | - |
| S32S-SCLCR/L09 | | 32 | 22 | 250 | 40 | 5° | - | - | CS35090 | FT-15 | - |
| S20R-SCLCR/L12 | CCMT1204 | 20 | 13 | 200 | 25 | 8° | - | - | CS40115 | FT-15 | - |
| S25R-SCLCR/L12 | | 25 | 17 | 200 | 32 | 8° | - | - | CS40115 | FT-15 | - |
| S32S-SCLCR/L12S | CCMT1204 | 32 | 22 | 250 | 40 | 6° | SMC-453 | SN630 | CS40145 | FT-15 | LW040 |
| S40T-SCLCR/L12S | | 40 | 27 | 300 | 50 | 4° | | | | | |