



▼Recommended Inserts 刀片建議品牌:KENNAMETAL/ACC

▼The specifications can be customized 規格可接受訂製

Insert: CNHU1005

Acceptable Customized Thickness 可訂製厚度: 12~18 mm

Order No.	Dimensions(mm)						
Right / Left	刀徑	切寬	最大切深	夾持接觸面直徑	孔徑		刃數
	DC	CW	CDX	DCSFMS	DCON	DCON(inch)	I No.
TSCN10-08014	80	14	18	44	27	1"	6
TSCN10-10014	100	14	26	48	27	1"	8
TSCN10-12514	125	14	35	55	32	1-1/4"	10
TSCN10-16014	160	14	46	68	40	1-1/2"	12
TSCN10-20014	200	14	61	78	50	2"	16
TSCN10-25014	250	14	82	86	50	2"	20

Insert: CNHU1205

Acceptable Customized Thickness 可訂製厚度: 15~22 mm

Order No.	Dimensions(mm)						
Right / Left	刀徑	切寬	最大切深	夾持接觸面直徑	孔徑		刃數
	DC	CW	CDX	DCSFMS	DCON	DCON(inch)	I No.
TSCN12-08018	80	18	18	44	27	1"	6
TSCN12-10018	100	18	26	48	27	1"	8
TSCN12-12518	125	18	35	55	32	1-1/4"	10
TSCN12-16018	160	18	46	68	40	1-1/2"	12
TSCN12-20018	200	18	61	78	50	2"	16
TSCN12-25018	250	18	82	86	50	2"	20

Insert: CNHU1606

Acceptable Customized Thickness 可訂製厚度: 20~29 mm

Order No.	Dimensions(mm)						
Right / Left	刀徑	切寬	最大切深	夾持接觸面直徑	孔徑		刃數
	DC	CW	CDX	DCSFMS	DCON	DCON(inch)	I No.
TSCN16-08022	80	22	18	44	27	1"	6
TSCN16-10022	100	22	26	48	27	1"	8
TSCN16-12522	125	22	35	55	32	1-1/4"	10
TSCN16-16022	160	22	46	68	40	1-1/2"	12
TSCN16-20022	200	22	61	78	50	2"	16
TSCN16-25022	250	22	82	86	50	2"	20

Order example: TSCN10-08014 x1"

ap (mm)	Insert	L (mm)	Screw	Wrench
13 ~ 17	CNHU1005 / CNHQ1005	10.0	CS40110	DT-15
17 ~ 21	CNHU1205 / CNHQ1205	12.7	CS40110	DT-15
21 ~ 30	CNHU1606 / CNHQ1606	16.0	CS50130	DT-20